



“DUMB WAITERS”

APPLICATION OF DUMB WAITER



Restaurants



Retail Outlet



Bar Room



Hotel Kitchen






Departmental Store



Penthouse

TECHNICAL SPECIFICATIONS



Capacity	Speed	Cabin Dimensions	Shaft. dims	Headroom	Serv. height
50-150	0.25m/s	Width - 400-700	+350	2900 OR	750 OR
		Depth - 400-700	+200	Door Ht.	Lowest Floor
		Height - 500-900	-	+1250	1/2 door ht. + 50
			+750		
200-300	0.25m/s	Width - 800-1000	+400	2900 OR	750
		Depth - 800-1000	+250	Door Ht.	Lowest Floor
		Height - 900-1200	-	+1250	1/2 door ht. + 50
			+750		

ATTENTION :
On cabin protection clear entrance dimensions resp. shaft dimensions will change
Minimum floor to floor height on doors in line = 2 x door height + 250 mm

Capacity	Speed	Cabin Dimensions	Shaft. dims	Headroom	PIT
50-150	0.25m/s	Width - 400-700	+350	2900 OR	1/2 dr ht. + 150
		Depth - 400-700	+200	Door Ht.	
		Height - 500-900	-	+1250	
			+750		
200-300	0.25m/s	Width - 800-1000	+350	2900 OR	1/2 dr ht. + 150
		Depth - 800-1000	+200	+1500	
		Height - 900-1200	-	+750	

ATTENTION :
On cabin protection clear entrance dimensions resp. shaft dimensions will change
Minimum floor to floor height on doors in line = 2 x door height + 250 mm

Capacity	Speed	Cabin Dimensions	Shaft. dims	Headroom	PIT
50-150	0.25m/s	Width - 400-700	+350	2900 OR	1/2 dr ht. + 150
		Depth - 400-700	+200	Door Ht.	
		Height - 500-900	-	+1250	
			+750		
200-300	0.25m/s	Width - 800-1000	+350	2900 OR	1/2 dr ht. + 150
		Depth - 800-1000	+200	+1500	
		Height - 900-1200	-	+750	

ATTENTION :
On cabin protection clear entrance dimensions resp. shaft dimensions will change

TECHNICAL SPECIFICATIONS



CAPACITY :

Range between 50 to 300 Kgs in increment of 50 Kgs

SPEED :

standard 0.25 MPS, higher speed available on customer requirements

DRIVE UNIT :

Traction Drive, High quality reduction worm gear coupled with motor & magnetic disc brake and handwheel.

HOISTWAY :

R.C.C. / Brickwall made by client or painted / zinc plated structure made of CR sheet profiles / Angles pre mounted in 2.5 mt. Long section on request.

CABIN :

Made of Stainless Steel sheet, MS sheet, Powder Coated/ galvanised, centered suspension, guided on both sides. Cars provided with removable self, and without door.

LANDING DOORS :

Made of Stainless Steel sheet, MS sheet, Powder Coated/ galvanised,

- ❖ Vertically opening Bi-parting/single sliding
- ❖ Single or Double hinged & wing door.

CONTROL :

- ❖ 24 Volt in all push buttons
- ❖ Call despatch on each landing
- ❖ Arrival buzzer and call signal
- ❖ Position indicator on each landing
- ❖ Over current protection
- ❖ Overload Indicator available on request

MACHINE ROOM :

No extra machine room is required for housing our machine, it can be fitted within height of top floor or within self supporting structure.

COMPLIANT :

our (service lift/dumb waiter) available in full compliance of IS 14665 of 2002.